



Sharp MultiSync® M862  
LCD 86" Message Large Format Display

## Preliminary Datasheet



### **Built to perform, designed to last**

The versatile solution for professional display applications, the Sharp MultiSync® M2 Series (32" up to 98") is purpose-built for demanding signage and meeting room environments. With native USB-C connectivity and broad compatibility with platforms such as Crestron, Cisco Webex, and Microsoft Teams, it enables seamless BYOD collaboration and future-ready integration, while 802.1x LAN support ensures enterprise-grade network security. Featuring class-leading 550 cd/m<sup>2</sup> brightness, a high-haze panel to minimise glare, and SpectraView Engine, the M2 Series delivers outstanding visual performance with unmatched colour precision.

Its proven modular design supports custom computing options (Raspberry Pi or Intel® SDM) and flexible connectivity (e.g. AV-over-IP), ensuring lasting versatility, performance, and sustainability.

### **Benefits**

**Seamless meeting workflows** - a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups. As the established standard for modern collaboration spaces, USB-C supports frictionless BYOD experiences.

**Unhindered readability** - a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment

**Security assured** - 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.

**Enhanced imaging precision** - when brand consistency and corporate identity are important, NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.

## Product Information

Product Name	Sharp MultiSync® M862
Model	PN-M862
Product Group	LCD 86" Message Large Format Display

## Display

Panel Technology	IPS with Direct LED backlights
Screen Size [inch/cm]	86 / 217.2
Aspect Ratio	16:9
Brightness [cd/m <sup>2</sup> ]	550
Contrast Ratio	1200:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Colour Gamut	72% of NTSC
Response Time (typ.) [ms]	8
Panel Refresh Rate [Hz]	60
Haze Level [%]	Pro (25)
Supported Orientation	Face Up <sup>1</sup> ; Landscape; Portrait

## Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	1024 x 768;	1366 x 768;	1920 x 1200;	720 x 400;
	1270 x 720;	1400 x 1050;	1920 x 1200;	720 x 480;
	1280 x 1024;	1440 x 900;	1920 x 2160;	720 x 576;
	1280 x 720;	1600 x 1200;	3840 x 2160;	800 x 600
	1280 x 800;	1680 x 1050;	4096 x 2160;	
	1360 x 768;	1920 x 1080;	640 x 480;	

## Synchronisation Rate

Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76

## Connectivity

HDMI IN 1	Video Input; UHD (60 Hz) HDCP (2.2); Audio Input; ARC; CEC
HDMI IN 2	Video Input; UHD (60 Hz) HDCP (2.2); Audio Input; CEC
HDMI OUT	Video Output; UHD (60 Hz) HDCP (2.2); Audio Output; Loop Through: HDMI IN 2, Option, Compute module

DP IN 1	Video Input; UHD (60 Hz) DP 1.2; HDCP (2.2); Audio Input
DP OUT	Video Output; UHD (60 Hz) DP 1.2; HDCP (2.2); Audio Output; Loop Through: DisplayPort IN, USB-C 2
USB-A 1	USB (2.0 / 3.2); 4.5 W; Peripherals; USB Storage
USB-A (Service)	2.5 W; Service
USB-C 1	Video Input; UHD (60 Hz); DP alt. 1.2; HDCP (2.2); Audio Input; USB 2.0 / 3.2; 65 W
USB-C 2	USB 2.0 / 3.2; 7.5 W; Peripherals; Storage
Audio Output (3.5 mm)	Audio Output; Line Out
LAN 1	100 MBit/s
LAN 2	Loop Through: LAN 1, RS-232C, IR; 100 MBit/s
RS-232C	9600 bps
Remote In (3.5 mm)	Eco Sensor (IR-Extender, Ambient and Presence)
Input Detect	Custom; Last; First
PiP / PbP	2-Split; Scalable picture size

## Calibration

Factory Calibration	Gamma; Intensity; RGB; Uniformity; White Point
Calibration with Software	Corner Uniformity; Gamma; Intensity; RGB; Update Factory Calibration; White Point
Calibration Software	Display Wall Calibrator

## Open Modular Intelligence

Intel® SDM	accepts Intel® Smart Display Modules Large and Small up to 66 W
Compute Module Slot	MPi4 and MPi5 Kit (powered by Raspberry Pi)

## Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

## Electrical

Power Consumption [W]	190 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC; 50/60 Hz; internal

## Environmental Conditions

---

Operating Temperature [°C]	+0 to +40
----------------------------	-----------

---

Operating Humidity [%]	20 to 80
------------------------	----------

---

Storage Humidity [%]	10 to 80
----------------------	----------

---

Storage Temperature [°C]	-20 to 60
--------------------------	-----------

---

## Mechanical

---

Dimensions (W x H x D) [mm]	1,927.6 x 1,099.1 x 83.2
-----------------------------	--------------------------

---

Weight [kg]	47
-------------	----

---

Bezel Width [mm]	14.3 (left, right and top); 14.8 (bottom)
------------------	---

---

VESA Mounting [mm]	4 holes; 600 x 400 (FDMI); M8
--------------------	-------------------------------

---

Ingress Protection	IP5x (front); IP2x (back)
--------------------	---------------------------

---

Packaging Dimensions (W x H x D) [mm]	2,090 x 1,225 x 225
---------------------------------------	---------------------

---

Packaging Weight [kg]	64
-----------------------	----

---

Material	Metal
----------	-------

---

## Additional Features

---

Special Characteristics	CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler
-------------------------	--

---

Colour Versions	Black Front Bezel, Black Back Cabinet
-----------------	---------------------------------------

---

Audio	Integrated Speakers (10 W + 10 W)
-------	-----------------------------------

---

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
------------------	--

---

Operating Hours	24/7
-----------------	------

---

External Control	AMX NetLinx Support; Crestron V2; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; SNMP
------------------	---

---

Remote Management	NaViSet Administrator 2
-------------------	-------------------------

---

Security	Disable HW Buttons; Disable IR Functionality; Emergency Notification; IEEE802.1X (LAN)
----------	--

---

<sup>1</sup> adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support

Design and specifications are subject to change without prior notice.